



5 Textures | 5 Sizes | 5/8" Thickness

12" x 24", 16" x 32", 18" x 36"

24" x 24", 36" x 36"

Featured: Aperte

DCOF Testing	Results	Test	Results	Sizes
Century DCOF	0.68	Compression Breaking Load	810 kg/cm ²	12" x 24" x 5/8" Chevron Tile 4" x 12"
Elektron DCOF	0.67	Compression B.L. after Freezing Test	750 kg/cm ²	16" x 32" x 5/8" Plank 8" x FL
Leather DCOF	0.58	Bending Strength	119 kg/cm ²	18" x 36" x 5/8" Tile 4" x 16"
Micro DCOF	0.60	Volumetric Weight	2710 kg/m ³	24" x 24" x 5/8" Hexagon Tile 8"
Monet DCOF	0.50	Water Absorption	0.01%	36" x 36" x 3/4" 2cm and 3cm Slabs Available
		Apparent Porosity	0.3%	Custom Sizes Available
		Thermal Linear Expansion Coefficient	8.7 106	Minimum order quantity - 500 sf
		Abrasion Test	2.2 mm	
		Impact Test	60 cm	Mosaics
		Freeze-Defreeze Cycles	24 Cycles	Random Interlocking Mosaic
		Microscopic Properties	Calcite - 99%	Stack 1" x 6"
			Quartz - 1%	Hexagon 4"
				Custom Patterns Available

Texture Options


Symbols




Century Texture




Elektron Texture



Leather Texture



Micro Texture



Monet Texture



Floor & Wall



Natural



Residential



Commercial