

Nick Papa

Color	Nick Papa
Size	7 x 48 in
Overall Thickness	3 mm (2 mm LPT / 1 mm dB pad)
Wearlayer Thickness	12 mil
Textures	Deep Wood Embossed
Edge	Micro-Beveled
Finish	Matte with TuffCoat
Install	Glue Down

Symbols	Test	Results
	ASTM F2421 Dimensional Tolerance	Pass
	ASTM F2199 Dimensional Stability	Pass
	ASTM F970 Static Load	0.001 inch (Pass)
	ASTM F1514 Heat Stability	5.0 (Pass)
	ASTM F1515 Light Stability	4.5 (Pass)
	ASTM F925 Chemical Resistance	Pass
	ASTM F386 Average Thickness	0.083 inch
	ASTM F410 Wear Layer Thickness	0.0112 inch/11.2 mil
	ASTM F3261 Thickness Swell	0%
	ISO 24337 Geometrical Characteristics	Pass
	US EPA 3052:1996 Heavy Metal Content	Not Detected
	Hexavalent Chromium (Cr VI)	Not Detected
	Soluble elements	Not Detected
	Phthalate Content	Not Detected
	ASTM F1914 ASTM F3261	
	Residual Indentation at 75 lbs.	0.006 inch (Pass)
	Surface Integrity	No puncture through layer/décor into rigid core

Size Options	dB Pad Thickness	Acoustical Testing	Acoustical Results
6"x36", 6"x48", 7"x48"	1mm	18" Open Web Truss (OWT) 6" Concrete Slab	IIC: 55 / STC: 60 IIC: 56 / STC: 52
	1.5mm	18" Open Web Truss (OWT) 6" Concrete Slab	IIC: 55 / STC: 60 IIC: 58 / STC: 52



TUFFPLANK

dB PLANK



LPT Plank

Size	7 x 48 in
Overall Thickness	3 mm (2 mm LPT / 1 mm dB pad)
Wearlayer Thickness	12 mil
Textures	Deep Wood Embossed
Edge	Micro-Beveled
Finish	Matte with TuffCoat
Install	Glue Down

Symbols	Test	Results
 	ASTM F2421 Dimensional Tolerance	Pass
	ASTM F2199 Dimensional Stability	Pass
	ASTM F970 Static Load	0.001 inch (Pass)
	ASTM F1514 Heat Stability	5.0 (Pass)
	ASTM F1515 Light Stability	4.5 (Pass)
	ASTM F925 Chemical Resistance	Pass
	ASTM F386 Average Thickness	0.083 inch
	ASTM F410 Wear Layer Thickness	0.0112 inch/11.2 mil
	ASTM F3261 Thickness Swell	0%
	ISO 24337 Geometrical Characteristics	Pass
	US EPA 3052:1996 Heavy Metal Content	Not Detected
	Hexavalent Chromium (Cr VI)	Not Detected
	Soluble elements	Not Detected
	Phthalate Content	Not Detected
	ASTM F1914 ASTM F3261	0.006 inch (Pass)
	Residual Indentation at 75 lbs.	No puncture through layer/décor into rigid core
	Surface Integrity	

Size Options	dB Pad Thickness	Acoustical Testing	Acoustical Results
6"x36", 6"x48", 7"x48"	1mm	18" Open Web Truss (OWT) 6" Concrete Slab	IIC: 55 / STC: 60 IIC: 56 / STC: 52
	1.5mm	18" Open Web Truss (OWT) 6" Concrete Slab	IIC: 55 / STC: 60 IIC: 58 / STC: 52