

Details	Technical Specific	ations & Features	Packing	Pcs/Box	SF/Box	Lbs/Box
Thermally modified wood mosaic tile	Thermal Modification	Process of treating the wood with a controlled pyrolysis for 2 -3 days.	16.10" x 9.29"	10pcs	10.4 SF	11 Lbs
Sheet Size: 16.10" x 9.29"		Through the Thermal Process, the wood's	Format			
Thickness: 3/8"	Fire Resistance	molecular structure is modified; all the organic compounds and water retained in the wood is removed.				
Grout free with 1mm gap between chips						
UV Clear Coat		Class C3				
Mesh Mounted		May be installed on a wall near electric fireplace with a temperature not to exceed 210°F.				
Benefits		Not recommended for installation on a wall near wood burning fireplace or stove.				
• Durable	Durability Recommended Adhesives	Class 1-3 EN 350-2				
Resistant to micro-organisms and insects		Mapei Ultrabond ECO GPT Mapei ECO 985 Boston Best Adhesive - Bond Hardwood Liquid Nails Heavy Duty - Construction Adhesive Loctite PL Premium Polyurethane Weldwood Contact Cement - Construction Adhesive For a more uniform result, use a brown color	Natural Wood			Wood
<ul> <li>Up to 90% reduced shrinking and swelling</li> </ul>			Symbols			
<ul> <li>Environmentally friendly No chemical staining</li> </ul>						
• 100% sourced in North America using sustainable		adhesive.	WF	${\mathbb C}$		
harvesting	Cleaning	Warm soapy water. Avoid chemical and abrasive products.	Wall Tile Resid	dential Comme	rcial Natural	
<ul> <li>Handmade in the USA</li> </ul>		products.				